Overview of Concept of Operations

NAJPTC Program


Outline

- Key System Requirements
- Overview of Concept of Operations
- Impact on Rules & Procedures

System Objectives

- Must not prevent any operation that can legitimately be performed today
- Shall be in conformance with all existing Operating Rules
- Must not be impose operating constraints not experienced today - must not be more cumbersome to use
- Design must be flexible and permit incremental implementation (migration)
- Must be cost-effective
- Shall support core PTC objectives

Overview of NAJPTC Territory



Note:

Spurs: non-controlled

Yard Tracks: non-controlled Industry Tracks: non-controlled

CTC Sidings: controlled

Scope of Operations

- Continuous display & enforcement of Authorities & Restrictions
 - 12 Passenger Locomotives (for high speed operation)
 - Chicago-St. Louis trains 110 mph
 - Texas trains 90 mph
 - Selected freight (particularly road switchers)
- Continuous text display of Authorities only (no enforcement)
 - 2 MoW Hirail Patrol Vehicles
 - 1 IDOT Hirail
- Accommodation for non-communicating trains

NAJPTC Functionality Included Trains

- Train Tracking
- Maintenance, Data Delivery & Continuous Display of Bulletins (Speed Management)
- Data Delivery & Continuous Display of Authorities (Authority Management)
- Route Integrity Monitoring
- Warnings & Enforcement of
 - Authority Limits
 - Speed Restrictions
 - Maintenance of Way Work Limits

NAJPTC Functionality Included Trains (cont.)

- Locomotive Switch Control
- Advance Activation of Crossing Warning Systems
- Interface with Train Defect Detectors
- Emergency Handling
- GCOR Rule 6.30 Protection of Entraining and Detraining Passengers
- Pacing

NAJPTC Functionality Included Roadway Worker Terminal

- Request Form A Speed Restrictions, Form B Work Limits & Release of Speed Restrictions (Speed Management)
- Data Delivery & Continuous Display of Authorities (Authority Management)
- Display of Emergency Warnings

Train Initialization

- Powering up locomotive system
 - All hardware checked automatically
 - All software checked for integrity
 - Software version number checked to verify it is current

Train Initialization (cont.)

- Train Initialization
 - CAD sends train consist to PTC
 - Default train data used initially until train length can be verified
 - Some manual entry required
 - train type
 - train orientation
 - track, if LDS cannot determine which track


Train Tracking

- All track circuits between adjacent signals are monitored
- All trains are tracked through monitoring track circuits
- Equipped trains have GPS/INS Location Determination System (LDS)
 - within 10 feet along the track
 - by track
- Reports train location on basis of time and events

Speed Management

- PTC maintains Permanent Civil Speeds
- Preparation & Distribution of Bulletins

Operating through Form B Work Limits



- Form B not displayed to Train A
- Form B displayed to Trains B & C
 - acknowledgement required
- Form B displayed to Train D
 - acknowledgement not required


Authority Management

- Signal-based Authorities
 - based on field signal indications matched to dispatcher switch & signal requests
 - Integrated Territory fixed block operation
 - authorities displayed to match authorities conveyed by wayside signals
 - Standalone Territory moving block operation
 - Authorities displayed in Cab
 - PTC Aspect for communicating trains
 - Non-communicating trains use conventional signal aspects


Authority Management (cont.)

- Forms-Based Authorities
 - Track and Time (Work Authorities)
 - Conveyed to both equipped trains and Roadway Workers
 - Permission to Pass Signal at Stop
 - Permission to Enter Main Track between Control Points

Authorities In Integrated Territory




Authorities In Standalone Territory



Role of Conventional Signaling


- Safety
 - Provides exclusive occupancy for train
 - Signal spacing based on worst braking train
- Operational
 - Provides movement authority to train




CBTC - Communications-Based Train Control

- Safety
 - Provides exclusive occupancy for train
 - Headway depends on braking capability
- Operational
 - Provides movement authority to train through incab display


Comparison of Headways Moving Block vs. Fixed Block




Comparison of CBTC & Conventional Signalling (1)




Comparison of CBTC & Conventional Signalling (2)




Comparison of CBTC & Conventional Signalling (3)




Comparison of CBTC & Conventional Signalling (4)




Comparison of CBTC & Conventional Signalling (5)




Comparison of CBTC & Conventional Signalling (6)




Comparison of CBTC & Conventional Signalling (7)




Comparison of CBTC & Conventional Signalling (8)




Comparison of CBTC & Conventional Signalling (9)




Comparison of CBTC & Conventional Signalling (10)




Comparison of CBTC & Conventional Signalling (11)




Comparison of CBTC & Conventional Signalling (12)




Comparison of CBTC & Conventional Signalling (13)




Comparison of CBTC & Conventional Signalling (14)




Comparison of CBTC & Conventional Signalling (15)




Comparison of CBTC & Conventional Signalling (16)



Comparison of CBTC & Conventional Signalling (17)



Comparison of CBTC & Conventional Signalling (18)



Advantages of Moving Block

- Treats each train uniquely
 - Result higher capacity
- Allows trains to bunch when operating more slowly
 - Temporary Speed Restrictions
 - Approaching Yards
 - Result higher capacity
- Train can leave siding sooner following overtake
 - Result better performance
- Overall result
 - Better asset utilization

Route Integrity Monitoring

- Correct position of power-operated switches will be verified as trains approach
 - if not verifiable, MA will be withdrawn to switch
- All hand-operated switches will be monitored through track circuits
 - any unidentified track occupancy results in Restricted Speed Restriction
- All hand-operated operated switches in highspeed territory electrically locked and individually monitored
 - Stop & Inspect Restriction applied if not properly aligned


Warnings and Enforcement

- General Principle Enforcement always preceded by visual & audible warnings
 - Exception emergency situation
- Enforcement of authorities
 - Warnings provide countdown till enforcement
 - Loco engineer actions may slow down or reverse countdown
- Speed enforcement
- Form B Work Limits
 - Train enforced to limits if presence of limits not acknowledged

Warnings and Enforcement (cont.)


- Enforcement is action of last resort
 - enforcement actions will be logged showing warning location, start of enforcement, stop, reason for enforcement
 - enforcements reported to CAD

Locomotive Switch Control



- Control of switch(es) must be given by Dispatcher
- Locomotive Switch Control within WAs only
- Loco HMI will display when switch is locked
 - Permission to pass Signal at Stop not required

Advanced Activation of Crossing Warning Systems



- Applies to all equipped trains
- If system not operational, Speed Restrictions applied
 - conventional speeds if WIU not operational
 - Restricted Speed if gates down too long

Interface with Train Defect Detectors

 Supplements normal voice-radio warnings with a message on the locomotive display


Emergency Handling

- Detection of Unauthorized or Runaway moves
- Prediction of Authority Violations
- Actions following Emergency Brake Applications

Detection of Unauthorized or Runaway moves


- Detected by two successive unexplained track occupancies
- Dispatcher notified
- Authority of affected trains reduced to nearest intervening control point if there is one
- Otherwise, authority removed to front of train
 - forces train to stop

System Response to Emergency Brake Application



 Restricted Speed Restriction automatically applied to Emergency Protection Limits for 10 Minutes

GCOR Rule 6.30 - Protection of Entraining and Detraining Passengers



Stop & Inspect Restriction

- •applied when passenger train slows to 15 mph within limits
- •removed when passenger train reaches 20 mph following stop

Can define applicable tracks

Pacing

- Demonstration only
 - CAD does not currently support
- Provides recommended speed of operation towards point of conflict
 - Allows for more fuel efficient operation
 - Pacing speed is advisory not instruction

Other System functions

- Health Reporting
- Data Logging

Impact on Operating Rules & Procedures

- System designed to be very similar to operations today
- Procedures for locomotive engineer data entries
- Locomotive Control of Switches
- New operating rules & procedures to handle system failures
 - communications
 - display
 - cutting out enforcement